

21. **Allowable Emissions:** The Permittee shall not allow emissions into the atmosphere to exceed any of the following:

	Daily Emission Limits	Twelve Month Rolling Average Emission Limits
Carbon Monoxide (CO)	1 pound	365 pounds
Oxides of Nitrogen (NO _x)	3 pounds	1095 pounds
Particulates Less than 10 Microns (PM ₁₀)	1 pound	365 pounds
Total Particulates	1 pound	365 pounds
Volatile Organic Compounds (VOCs)	1 pound	365 pounds
Solvent	pounds	pounds

The twelve month rolling average shall be calculated at the end of each calendar month by summing the emissions over the most recent twelve calendar months.

The Permittee shall limit the consumption of petroleum solvent to gallons per month and gallons per year.

22. **Operating Requirements** - The Permittee shall not operate any petroleum solvent dry cleaning facility unless all of the following requirements are satisfied:
- The dry cleaning equipment shall not be operated with perceptible leaks from any portion of the equipment, including but not limited to: hose connections, unions, couplings and valves; machine door gaskets and seating; filter head gaskets and seating; pumps; base tanks and storage containers; water separators; filter sludge recovery; distillation units; diverter valves; solvent-moistened lint from a lint basket; and cartridge filters.
 - All solvents shall be stored in closed containers.
 - All washer and dryer traps, access doors, and any other parts of equipment where solvent may be exposed to the atmosphere, shall be kept closed at all times except when required for proper operation or maintenance.
 - Any petroleum filtration system shall be installed and operated to comply with at least one of the following:
 - Reduce the volatile organic compounds in all filtration wastes to 2.2 lbs (1 kg) or less per 220 lbs (100 kg) dry weight of

- articles cleaned, before disposal, and exposure to the atmosphere; or
2. Operate a cartridge filtration system, and drain the filter cartridges in their sealed housings for eight hours or more before their removal; or
 3. Place all discarded filtration material, including cartridges and particulate filter media, immediately in sealed containers and dispose of according to hazardous waste statutes.
23. **Record keeping:** The Permittee shall keep daily records of the weight of clothing cleaned, the amount of solvent added and the weight and type of any material disposed of which contains any quantity of cleaning solvent. The name of the company receiving the disposed material shall also be recorded. These records must be maintained in a readily accessible location for a minimum of three years and must be made available to a representative of the Control Officer upon verbal or written request.